

## IR DOME CAMERA

**TP-101IR** Entry-Level IR Dome Camera



### FEATURES:

- Rotatable Housing for easy installation
- 12 IR LED's for night viewing range 10M
- With built-in 4mm fixed lens
- Elegant design with low cost

### SPECIFICATIONS

SPECIFICATIONS	
SENSOR	1/3" INTERLINE TRANSFER CCD
NUMBER OF PIXELS	NTSC: 512(H)*492(V)/PAL :512(H)*582(V)
HORIZONTAL RESOLUTION	More than 420 TV lines
SCANNING SYSTEM	2:1 Interlace
SENSITIVITY	0.2 LUX / F2.0
SYNCHRONIZATION	Internal
S/N RATIO	More than 48dB
GAMMA CORRECTION	0.45
ELECTRONIC SHUTTER	Auto and up to 1/100,000
VIDEO OUTPUT	1 Vp-p, 75 Ohm Composite
LENS	4mm Board lens (standard) optional: 6mm 8mm
IR LED	850nm x 12 pcs
POWER SUPPLY	DC 12V (-/+10%)
POWER CONSUMPTION	IR on : 3.2w(250mA) ; IR off : 1w (80mA)
WHITE BALANCE	ATW WITH MCT TECHNOLOGY(MULTI-COLOR TEMP)
AUTO GAIN CONTROL	Full Auto
BACK LIGHT COMPENSATION	Full Auto
APERTURE CORRECTION	2H Mode of H. aperture correction
DIMENSION H*D mm	114 $\phi$ x 80(L) mm
NET WEIGHT	143g
OPERATING TEMPERATURE	-10 to +45 Degree C